Residential Energy Storage System (Low Voltage & Stackable) SOL-5-5.6LS







High Efficiency Max. efficiency 94%



Easy installation



Safety and Reliability Lithium-ion phosphate battery cells



System integration Integrated design, plug and play, no compatibility issues

Product Information



Self-Consumption Optimization



Maximum flexibility for any applications with up to 12

modules connected in parallel



Integrated with inverter to avoid the compatibility problem



LFP battery, safety and long cycle life

Stackable design, effortlessly installation



Capable of High-Powered Emergercy-Backup and Off-Grid Function

[4] Battery Module

- 5.12 kWh per Module
- Modular and Stack Installation Design to simplify the maintenance
- Connect up to 12 module in parallel for a maximum size of 60 kWh



Flexible, Efficient, Simple

	
•	

Plug Connection No Additional Wiring Required



5-60KWH Tailored Sizing for Each Application

	*	
Exter	nd Δn	vtimo
	IC AIL	yunic
		-

Easily Adapts to New Requirements

4		

High Power Power for Every Application

Technical Parameters			
Inverter	SOL-5.6KL-S		
Rated Power	5600W		
Maximum PV Array Open Circuit voltage	500VDC		
MPPT Voltage Range	120-450V		
Nomial Output Voltage	220/230/240VAC		
Output Voltage Range	184-265VAC		
Nominal Output Current	25.5A/24.3A/23.3A		
Efficiency	Up to 93.5%		
Grid Output Voltage Range	120-280VAC		
Grid Frequency	50/60Hz(Auto Sensing)		
Maximum AC Charge Current	120A		
Maximum Solar Charge Current	120A		
Nominal DC Voltage	48VDC		
Battery Model	SOL-51.2/100-L		
Combination Method	16S1P		
Rated Capacity	Typical	100Ah	
	Minimum	98Ah	
Rated Voltage	51.2V		
Limited Discharge Voltage	43.2V		
Limited Charge Voltage	57.6V		
Internal Resistance(single battery pack)	≤20mΩ		
Max Continuous Charging Current	100A		
Max Continuous Discharging Current	100A		
Operation Temperature Range	Charge:0~50 ℃/ Discharge: -10~50 ℃		
Storage Temperature Range	-20~+60°C,Recommend: ≤60±25%RH storage humidity		
Single Module Size/weight	680*429*215mm /50Kg±1Kg		
Overall Size/weight	680*429*540mm /85Kg±1Kg		